



Fire Hydrant Equipment Breaching Inlet & Cabinets



2 Way Breaching Inlet

Model	BI 2
Inlet	Ø65 mm Male Copper Alloy Inst. Non Return Valve
Outlet	100 mm Flanged to EN 1092-2
Pressure Rating	PN 16
Test Pressure	20 bar
Overall Width	279 mm
Overall Height	215 mm
Overall Weight	17 kg
Body Material	Ductile Iron / Cast Iron**
Cap	Plastic with chromed chained
Paint Finishing*	RAL 3000 Flame Red Epoxy Polyester Powder Coating
Manufactured & Certified to	BS 5041 Part 3

*Yellow finishing available upon request

**Factory tested



4 Way Breaching Inlet

Model	BI 4
Inlet	Ø65 mm Male Copper Alloy Inst. Non Return Valve
Outlet	150 mm Flanged to EN 1092-2
Pressure Rating	PN 16
Test Pressure	20 bar
Overall Width	285 mm
Overall Height	215 mm
Overall Weight	33 kg
Body Material	Ductile Iron / Cast Iron**
Cap	Plastic with chromed chained
Paint Finishing*	RAL 3000 Flame Red Epoxy Polyester Powder Coating
Manufactured & Certified to	BS 5041 Part 3

*Yellow finishing available upon request

**Factory tested



2 Way Breaching Cabinet

Model	BC-2M
Body Material	1.2 mm Mild Steel Sheet
Dimension	595 mm x 364 mm x 295 mm
Glass	Clear Glass
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating
Manufactured to	BS 5401 Part 5



4 Way Breaching Cabinet

Model	BC-4M
Body Material	1.2 mm Mild Steel Sheet
Dimension	582 mm x 564 mm x 295 mm
Glass	Clear Glass
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating
Manufactured to	BS 5401 Part 5

Top Techno Fire & Safety Co. LLC

