



EMERGENCY EXIT SIGN



BY-B5108U-G/R

TECHNO



Features

- ▶ Super bright&Long Lasting LEDs
- ▶ Dual 120V/277V AC input
- ▶ Test switch and AC-ON indicator included
- ▶ Overcharge&Over-discharge protection
- ▶ Universal mounting:Wall/Ceiling/Flag Mounting
- ▶ Single/Double face
- ▶ White/Black Body available
- ▶ Overcharge&Over-discharge protection




BY-B5108U-G




BY-B5108U-R

Product Size



Unit:mm

Light Distribution Curve



Product parameters

Model Name	BY-B5108U-R	BY-B5108U-G
Input Voltage	AC120/277V, 60Hz, 200mA	AC120/277V, 60Hz, 200mA
Light Source	RED DIP5mm(12pcs)	RED DIP5mm(12pcs)
Input Power	3.5W	3.5W
Emergency Power	0.36W	0.36W
Operation Mode	Maintained	Maintained
Emergency Duration	90 Minutes	90 Minutes
Emergency Luminance Flux	/	/
Recharge Time	24 Hrs	24 Hrs
Battery	Ni-Cd 3.6V, 900mAh	Ni-Cd 3.6V, 900mAh
Battery Life	Up to 4 years	Up to 4 years
Use Environment	Damp Locations	Damp Locations
Operation Temp Range	0 °C -40 °C	0 °C -40 °C
Remote Capable	/	/
Max. mounting height	/	/

Top Techno Fire & Safety Co. LLC

