



Dekon Conventional Fire Alarm System

Model No: D-KA316 Conventional Fire Alarm Control Panel



DESCRIPTION

D-KA316 16 Zone Conventional Fire Alarm Control Panel are designed by the leading technology and microprocessor-based devices. The devices are user-friendly and simple to understand. DEKON D-KA316 is 16 Zone Conventional Fire Alarm Panels.

All the system conditions are displayed on the central LCD and via separate indicator leds as well. The central supervises system troubles and conditions and displays to the user. By the Reset, Alarm, Cancel Alarm, Silence, Test and Evacuate buttons user can perform simply the system functions. The general system indicators: Power, Ready, Pre-alarm, Fire Alarm, Cancel Alarm, Silence and Evacuate indicator leds are displayed on the left hand of central and the Trouble indicator leds are Ac Loss, Battery Error, Siren Error, Line Cut and Line Short indications are displayed in the right hand on the central.

On both devices there separate auxiliary power outputs 24V. For installation of additional functional devices there is no need an additional power source as they are available onboard.

The devices are manufactured in SMD Technology and compile with EN 54-2/4 standard. The centrals are compatible with all detectors and devices that comply with EN54 standards.

FEATURES

- 16 Zones.
- 2x16 Alphanumeric LCD Display.
- Alarm, Short circuit and Open circuit indication.
- Plastic front Case.
- Metal Body.
- User friendly installation and programming.
- Day/Night Mode.
- Non-volatile System Clock.
- 1 Supervised Siren Out.
- Alarm and Error relay Outputs.
- 24V Auxiliary Power Outputs.
- EN54-2/4 Compatible.
- Dimensions: 29x33,5x10,5cm; Weight: 3100 gr.

CERTIFICATES



Top Techno Fire & Safety Co. LLC

