



Stored Pressure Type ABC Dry Powder Portable Fire Extinguishers



KM 61549



0038

FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EED-1

EED-2

EED-2h

EED-3

EED-4N

EED-6

EED-9

EED-12

Model	EED-1	EED-2	EED-2h	EED-3	EED-4N	EED-6	EED-9	EED-12
Type	Stored Pressure Type							
Extinguishant	ABC Dry Powder							
Capacity	1 kg	2 kg	2 kg	3 kg	4 kg	6 kg	9 kg	12 kg
Propellant	Dry Nitrogen (N ₂)							
Valve	Controllable Non Ferrous Valve with Pressure Indicator							
Body Diameter	79 mm	110 mm	110 mm	130 mm	158 mm	158 mm	178 mm	188 mm
Overall Height	325 mm	370 mm	410 mm	425 mm	475 mm	525 mm	587 mm	695 mm
Approx Full Weight	1.8 kg	3.3 kg	3.4 kg	5.0 kg	6.9 kg	9.3 kg	13.1 kg	17.6 kg
Working Temperature Range	-20°C to +60°C							
Working Pressure	12 bar							
Test Pressure	25 bar							
Burst Pressure	Exceeds 69 bar							
Approx Discharge Range	2 m	2.5 m	2.5 m	4 m	5 m	5 m	7 m	7 m
Approx Discharge Time	11 sec	16 sec	11 sec	12 sec	18 sec	16 sec	18 sec	30 sec
Fire Rating	5A:34B	13A:55B	13A:70B	13A:89B	21A:113B	43A:233B	43A:233B	43A:233B
Fire Class	A, B, C + Electrical							
Internal Coating	Stoving Epoxy Primer							
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating							
Mounting	Plastic Bracket			Metal 'L' Wall Bracket				
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006 and BS EN 3-10: 2009							

Top Techno Fire & Safety Co. LLC

