



Stored Pressure Type AFF Foam & Water Portable Fire Extinguishers



KM 61549



0038

FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EEF-2s

EEF-6s

EEF-9s

EEW-6s

EEW-9s

Model	EEF-2s	EEF-6s	EEF-9s	EEW-6s	EEW-9s
Type	Stored Pressure Type				
Extinguishant	AFF Foam (Premix)			Water	
Capacity	2 litres	6 litres	9 litres	6 litres	9 litres
Propellant	Nitrogen (N ₂)				
Valve	Controllable Chrome Plated Brass Valve with Pressure Indicator				
Body Diameter	110 mm	158 mm	178 mm	158 mm	178 mm
Overall Height	398 mm	575 mm	625 mm	575 mm	625 mm
Approx Full Weight	3.7 kg	10.0 kg	13.7 kg	10.0 kg	13.7 kg
Working Temperature Range	+ 5°C to + 60°C				
Working Pressure	12 bar				
Test Pressure	25 bar				
Burst Pressure	Exceeds 69 bar				
Approx Discharge Range	1.5 m	4 m	6 m	4 m	6 m
Approx Discharge Time	15 sec	32 sec	57 sec	41 sec	75 sec
Fire Rating	5A:34B	13A:144B	21A:183B	13A	21A
Fire Class	A, B + Electrical Safety Test*			A + Electrical Safety Test*	
Internal Coating	Thermoplastic Powder Coating (PPA)				
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating				
Mounting	Wire Bracket	Metal 'L' Wall Bracket			
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006, and BS EN 3-10: 2009				

* Safe if in accidental contact with live electrical equipment. Comply with electrical conductivity test BS EN 3-7, Clause 9 Annex C

Top Techno Fire & Safety Co. LLC

