



Cartridge Operated Type AFF Foam & Water Portable Fire Extinguishers



FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EEF-6cs

EEF-9cs

EEF-9c

EEW-6cs

EEW-9cs

Model	EEF-6cs	EEF-9cs	EEF-9c	EEW-6cs	EEW-9cs
Type	Cartridge Operated Type				
Extinguishant	AFF Foam (Premix)			Water	
Capacity	6 litres	9 litres	9 litres	6 litres	9 litres
CO ₂ Gas Cartridge	55 g	75 g	75 g	55 g	55 g
Valve / Headcap	CE Marked Controllable Chrome Plated Brass Headcap with Safety Relief Valve				
Body Diameter	158 mm	178 mm	178 mm	158 mm	178 mm
Overall Height	585 mm	630 mm	630 mm	585 mm	630 mm
Approx Full Weight	11.1 kg	14.9 kg	14.9 kg	11.1 kg	14.8 kg
Working Temperature Range	+ 5°C to + 60°C				
Working Pressure	12 bar				
Test Pressure	25 bar				
Burst Pressure	Exceeds 69 bar				
Approx Discharge Range	4 m	6 m	6 m	4 m	6 m
Approx Discharge Time	58 sec	88 sec	42 sec	38 sec	49 sec
Fire Rating	13A:144B	21A:183B	13A:183B	13A	21A
Fire Class	A, B + Electrical Safety Test*		A, B	A + Electrical Safety Test*	
Internal Coating	Thermoplastic Powder Coating (PPA)				
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating				
Mounting	Metal 'T' Wall Bracket				
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006 and BS EN 3-10: 2009				

* Safe if in accidental contact with live electrical equipment. Comply with electrical conductivity test BS EN 3-7, Clause 9 Annex C

Top Techno Fire & Safety Co. LLC

