



## Cartridge Operated Type Wet Chemical Portable Fire Extinguishers



KM 61549



0038

### FEATURES

- ✓ Fully deep drawn from cold rolled steel
- ✓ Externally coated with polyester powder
- ✓ Pressure tested to twice the extinguisher's working pressure



EEK-6cs



EEK-9cs

Model	EEK-6cs	EEK-9cs
Type	Cartridge Operated Type	
Extinguishant	Wet Chemical	
Capacity	6 litres	9 litres
CO2 Gas Cartridge	35 g	55 g
Valve / Headcap	CE Marked Controllable Chrome Plated Brass Headcap with Safety Relief Valve	
Body Diameter	158 mm	178 mm
Overall Height	585 mm	630 mm
Approx Full Weight	13.4 kg	18.7 kg
Working Temperature Range	0°C to +60°C	
Working Pressure	12 bar	
Test Pressure	25 bar	
Burst Pressure	Exceeds 69 bar	
Approx Discharge Range	>2 m	
Approx Discharge Time	70 sec	84 sec
Fire Rating	8A:75F	13A:75F
Fire Class	A, F + Electrical Safety Test*	
Internal Coating	Thermoplastic Powder Coating (PPA)	
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating	
Mounting	Metal 'T' Wall Bracket	
Manufactured & Certified to	BS EN 3-7: 2004 + A1: 2007, BS EN 3-8: 2006 and BS EN 3-10: 2009	

\* Safe if in accidental contact with live electrical equipment. Comply with electrical conductivity test BS EN 3-7, Clause 9 Annex C

\* Overall height measure from bottom upto valve handle

**Top Techno Fire & Safety Co. LLC**

