



## Fire Hose Reels Accessories



### Fire Reel Hose

Model	FRH-19RS	FR-25*	FRH-25RS	FRH-25BS
Size	Ø 19 mm	Ø 25 mm	Ø 25 mm	Ø 25 mm
Colour	Red	Black	Red	Black
Surface	Smooth	Rough	Smooth	Smooth
Inner Diameter (ID)	19 mm	25 mm	25 mm	25 mm
Standard Length	30 m	30 m	30 m	30 m
Working Pressure at 20°C	12 bar	12 bar	12 bar	12 bar
Burst Pressure at 20°C	> 42 bar	> 42 bar	> 42 bar	> 42 bar
Manufactured & Certified to	EN 694	MS 1488	EN 694	EN 694

\* SIRIM Approved only

Note: Hose length, colour and surface options available upon request

Jet Spray Nozzle



EZ-19P  
EZ-25P

Jet Spray Nozzle



EZ-19  
EZ-25

Jet Nozzle



EZ-19J  
EZ-25J

Lever Operated Nozzle



EZ-19LO  
EZ-25LO

Jet Spray Nozzle



EZ-19OR

### Hose Nozzle

Model	EZ-19P	EZ-25P	EZ-19	EZ-25	EZ-19J	EZ-25J	EZ-19LO	EZ-25LO	EZ-19OR
Inlet	19 mm	25 mm	19 mm	25 mm	19 mm	25 mm	19 mm	25 mm	19 mm
Body Material	Nylon				Brass				
Finishing	Red				Chromed Plated				
Working Pressure	12 bar								
Test Pressure	18 bar								
Flow Rate @ 6 bar	Jet : 55L / min & Spray : 63L / min								
Throw Range @ 4 bar	Jet : 10 m & Spray : 4 m								

**Top Techno Fire & Safety Co. LLC**

