




Fire Hydrant Equipment Lay Flat Fire Hoses



Type 1 & Type 3 Fire Hose

Model	T110-65	T113-50	T113-65	T116-50	T116-65	T316-65
Type			Type 1			Type 3
Size	65 mm	50 mm	65 mm	50 mm	65 mm	65 mm
Standard Length	30 m					
Coupling	Instantaneous LA Coupling / GOST Coupling					
Working Pressure	10 bar	13 bar		16 bar		
Test/Burst Pressure	15 bar / 30 bar	26 bar / 39 bar		16 bar / 32 bar		24 bar / 48 bar
Colour	White					Red
Material	Canvas					Rubber
Manufactured to	BS 6391					

Note: Various hose length and coupling type available upon request



Lay Flat Canvas Fire Hose

Model	SH10-38E	SH14-38E	SH10-65E	SH14-65E	DH21-38E	DH21-65E	SH15-38P	SH15-52P	SH15-38E	SH15-52E
Type	Single Jacket				Double Jacket		Single Jacket			
Size	38 mm		65 mm		38 mm	65 mm	38 mm	52 mm	38 mm	52 mm
Standard Length	50' / 75' / 100'				20 m / 25 m / 30 m / 40 m					
Coupling	Instantaneous LA Coupling									
Working Pressure	10 bar	14 bar	10 bar	14 bar	21 bar	21 bar	15 bar	15 bar	15 bar	15 bar
Burst Pressure	31 bar	42 bar	31 bar	42 bar	63 bar	63 bar	45 bar	45 bar	45 bar	45 bar
Inner Material	EPDM						PVC		EPDM	
Outer Material	Polyester									
Colour	White									
Manufactured & Certified to	NFPA 1961 UL Listed						EN 14540 MED			

Note: Various hose length and coupling type available upon request

Top Techno Fire & Safety Co. LLC





Fire Hydrant Equipment Aluminium Jet Nozzle



Jet Nozzle Complete With Branchpipe

Model	JSN-001-AL
Body Material	Aluminium Alloy to BS 1490
Finishing	Natural
Inlet Size	Male Instantaneous BS 336
Flow Rate @ 65 PSI	210 L / min @ 12 mm Diameter 510 L / min @ 19 mm Diameter
Throwrange @ 65 PSI	16 m @ 12 mm Diameter 22 m @ 19 mm Diameter



Jet / Spray Diffuser Nozzle (Standard)

Model	JSN-003-AL-S
Body Material	Aluminium Alloy to BS 1490
Finishing	Natural
Inlet Size	Male Instantaneous BS 336
Flow Rate @ 65 PSI	500 L / min (Jet) 590 L / min (Spray)
Throwrange @ 65 PSI	26 m (Jet) 15 m (Spray)



Jet / Spray Diffuser Nozzle Complete With Branchpipe

Model	JSN-004-AL-S-BP
Body Material	Aluminium Alloy to BS 1490
Finishing	Natural
Inlet Size	Male Instantaneous BS 336
Flow Rate @ 65 PSI	500 L / min (Jet) 590 L / min (Spray)
Throwrange @ 65 PSI	26 m (Jet) 15 m (Spray)



Jet / Spray Nozzle Complete With Control Valve

Model	JSN-007-AL-CV-065
Body Material	Aluminium Alloy to BS 1490
Finishing	Natural
Inlet Size	2 1/2" BSP Male Instantaneous BS 336
Flow Rate @ 65 PSI	160 L / min (Jet) 140 L / min (Spray)
Throwrange @ 65 PSI	14 m (Jet/Spray)



Jet / Spray Nozzle Complete With Control Valve (Screw Thread)

Model	JSN-007-AL-CV-050
Body Material	Aluminium Alloy to BS 1490
Finishing	Natural
Inlet Size	2" BSP Male Thread
Flow Rate @ 65 PSI	160 L / min (Jet) 140 L / min (Spray)
Throwrange @ 65 PSI	14 m (Jet/Spray)

Top Techno Fire & Safety Co. LLC

