



Fire Hydrant Equipment Fire Hose Rack Assembly & Components



The **EVERSAFE** Fire Hose Rack Assembly is used to provide immediate and efficient water source for fire suppression, and permits one-man operation. The assembly is for occupants use, Class II service under NFPA 14 standard class of service. The pin rack features an automatic release mechanism where water flow through the hose after the last fold is released.



Fire Hose Rack Assembly 1 1/2"



Fire Hose Rack Assembly 2 1/2"

Fire Hose Rack Assembly 1 1/2" & 2 1/2"

Model	HRA-38-AV-JS	HRA-38-RV-JS	HRA-65-AV-JS	HRA-65-RV-JS
Description	1 1/2" Hose Rack Assembly c/w Angle Valve	1 1/2" Hose Rack Assembly c/w Pressure Reducing Valve	2 1/2" Hose Rack Assembly c/w Angle Valve	2 1/2" Hose Rack Assembly c/w Pressure Reducing Valve
Hose Release Mechanism	Automatic			
Hose Valve Type	1 1/2" Angle Hose Valve	1 1/2" Pressure Reducing Valve	2 1/2" Angle Hose Valve	2 1/2" Pressure Reducing Valve
Fire Hose Type	1 1/2" Polyester Single Jacket Rack Hose with EPDM Lining and Filament Polyester Yarn		2 1/2" Polyester Single Jacket Rack Hose with EPDM Lining and Filament Polyester Yarn	
Nozzle Type	1 1/2" Portable Jet/Spray Nozzle		2 1/2" Portable Jet/Spray Nozzle	
Hose Size	1 1/2" x 100 ft		2 1/2" x 100 ft	
Hose Colour	White			
Service Pressure	200 psi			
Burst Pressure	600 psi			

Note: UL/FM approved components

Lay Flat UL Fire Hose



Model	SH14-38ET	SH14-65ET
Type	Single Jacket	
Size	38 mm	65 mm
Standard Length	50' / 75' / 100'	
Coupling	NH Threaded Coupling	
Working Pressure	200 psi	
Burst Pressure	600 psi	
Inner Material	EPDM	
Outer Material	Polyester	
Colour	White	
Manufactured & Certified to	NFPA 1961 UL Listed	

Top Techno Fire & Safety Co. LLC

