






Fire Hose Reels Manual Swing Type Fire Hose Reels - Die Cast



SWING



CLOSE



RECESS

Manual Swing Type Fire Hose Reels - Die Cast

Model	EH19-SDM-09GI*	EH25-SDM-09GI**	EH25-SDM-12GI***
Disc Diameter	565 mm	565 mm	565 mm
Inlet Connection	Die Cast Swing Arm 1" BSP		
Hose Size (Ø x Length)	19 mm x 30 m	25 mm x 30 m	25 mm x 30 m
Swing Dimension (A x B x C)	495 mm x 565 mm x 160 mm	525 mm x 565 mm x 190 mm	525 mm x 565 mm x 190 mm
Close Dimension (A x B x C)	250 mm x 565 mm x 160 mm	280 mm x 565 mm x 190 mm	280 mm x 565 mm x 190 mm
Recess Dimension (L x W x D)	700 mm x 700 mm x 290 mm	760 mm x 760 mm x 320 mm	760 mm x 760 mm x 320 mm
Maximum Working / Test Pressure	12 bar / 18 bar	12 bar / 18 bar	12 bar / 18 bar
Standard Nozzle Type	Brass or Nylon Jet / Spray Nozzle		
Nozzle Orifice	6 mm	7 mm	7 mm
Minimum Flow Rate @ 4 bar	34 L / min	44 L / min	44 L / min
Drum Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating		
Manufactured & Certified to	EN 671-1 : 2012	MS 1447-1 : 2006	EN 671-1 : 2012

* TUV SUD PSB Approved only

** SIRIM and Bomba Approved only

*** CE or TUV SUD PSB Approved only

Note: 1. Various types of nozzle and hose length available upon request. Please refer to nozzle section for selection of nozzle

2. Horizontal bar hose reel available upon request

3. Ø 590mm disc available upon request

Top Techno Fire & Safety Co. LLC

