






Fire Hose Reels Manual Swing Type Fire Hose Reels - Hose Inlet



SWING



CLOSE



RECESS

Manual Swing Type Fire Hose Reels - Hose Inlet

Model	EH19-SHM-09BR*	EH25-SHM-09BR*	EH25-SHL-12BR**
Disc Diameter	565 mm	565 mm	590 mm
Inlet Connection	Hose 25 mm x 1 m	Hose 25 mm x 1 m	Hose 25 mm x 1 m
Hose Size (Ø x Length)	19 mm x 30 m	25 mm x 30 m	25 mm x 30 m
Swing Dimension (A x B x C)	525 mm x 565 mm x 160 mm	555 mm x 565 mm x 190 mm	525 mm x 590 mm x 145 mm
Close Dimension (A x B x C)	220 mm x 565 mm x 160 mm	250 mm x 565 mm x 190 mm	210 mm x 590 mm x 145 mm
Recess Dimension (L x W x D)	700 mm x 700 mm x 250 mm	700 mm x 700 mm x 290 mm	730 mm x 730 mm x 225 mm
Maximum Working / Test Pressure	12 bar / 18 bar	12 bar / 18 bar	12 bar / 18 bar
Standard Nozzle Type	Brass or Nylon Jet / Spray Nozzle		
Nozzle Orifice	6 mm	7 mm	7 mm
Minimum Flow Rate @ 4 bar	34 L / min	44 L / min	44 L / min
Drum Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating		
Manufactured & Certified to	EN 671-1 : 2012		

* CE or TUV SUD PSB Approved only

** CE Approved only

Note: 1. Various types of nozzle and hose length available upon request. Please refer to nozzle section for selection of nozzle
2. Horizontal bar hose reel available upon request
3. Ø 590mm disc available upon request

Top Techno Fire & Safety Co. LLC

