



Stored Pressure Type Carbon Dioxide Mobile Fire Extinguishers



KM 544838



0038



MCO-10



MCO-20



MCO-10T

Model	MCO-10	MCO-20	MCO-10T
Capacity	10 kg	20 kg	10 kg x 2
Style	Single		Twin
Extinguishant	Carbon Dioxide (CO ₂)		
Operating Head	Pai Mark (TPED) Brass Screw Down Valve with Safety Relief Valve		
Cylinder Thread	25E		
Discharge Hose	High Pressure Hose		
Hose Internal Diameter x Length	9.5 mm x 6 m*		
Discharge Horn	Plastic with On / Off Valve		
Cylinder Specification	EN ISO 9809-1 TPED	EN 1964 Part 1 TPED	EN ISO 9809-1 TPED
- Diameter	156 mm	229 mm	156 mm
- Nominal Height	990 mm	1210 mm	990 mm
Frame Work	Steel pipe / Flat Bar		
Overall Height	1065 mm	1210 mm	1040 mm
Overall Width	465 mm	565 mm	515 mm
Overall Depth	860 mm	1260 mm	1050 mm
Approx Empty Weight	33 kg	80 kg	50 kg
Approx Full Weight	43 kg	100 kg	70 kg
Cylinder / Frame Finish	RAL 3000 Flame Red Epoxy Polyester Powder Coating		
Wheel Diameter	300 mm		
Working Temperature Range	- 20°C to + 60°C		
Working Pressure	56 bar		
Cylinder Test Pressure	250 bar		
Approx Discharge Time	53 sec	61 sec	83 sec
Approx Discharge Range	4 m		
Fire Rating	70B	89B	89B
Fire Class	B + Electrical		
Manufactured & Certified to	BS EN 1866 : 2007		

* 30 meter hose length available on request

Top Techno Fire & Safety Co. LLC

