



Stored Pressure Type / Cartridge Operated Type ABC Dry Powder Mobile Fire Extinguishers



KM 544838



0038



Top View



Back View



MPM-25

MPM-50

MPG-25

MPG-50

Model	MPM-25	MPM-50	MPG-25	MPG-50
Type	Stored Pressure Type		Gas Cartridge Type	
Extinguishant	ABC Dry Powder			
Capacity	25 kg	50 kg	25 kg	50 kg
Propellant	Nitrogen (N ₂)		Carbon Dioxide (CO ₂)	
Valve / Headcap	Brass Valve with Pressure Gauge		Brass Headcap with Safety Relief Valve	
CO ₂ Cartridge	N/A		0.55 kg	1 kg
Discharge Hose	13 mm x 6 m	16 mm x 6 m	13 mm x 6 m	16 mm x 6 m*
Wheel Diameter	300 mm			
Frame Work	Steel Pipe / Flat Bar			
Cylinder Material	Steel			
Body Diameter	250 mm	386 mm	250 mm	386 mm
Overall Height	895 mm	975 mm	895 mm	975 mm
Overall Width	460 mm	570 mm	460 mm	570 mm
Overall Depth	550 mm	730 mm	550 mm	730 mm
Approx Empty Weight	22 kg	39 kg	28 kg	43 kg
Approx Full Weight	47 kg	89 kg	53 kg	93 kg
Working Temperature Range	- 20°C to + 60°C			
Working Pressure	12 bar			
Test Pressure	21.5 bar			
Safety Valve Lift Pressure	17 - 21 bar		18 - 20 bar	
Approx Discharge Time	48 sec	61 sec	52 sec	71 sec
Approx Discharge Range	9 m	10 m	9 m	11 m
Fire Rating	A IB C	A IIB C	A IB C	A IIB C
Fire Class	A , B, C + Electrical			
Paint Finishing	RAL 3000 Flame Red Epoxy Polyester Powder Coating			
Manufactured & Certified to	BS EN 1866 : 2007			

* 10 meter hose length available on request

Top Techno Fire & Safety Co. LLC

