



Fire Hydrant Equipment Fire Hydrants



2 Way Fire Hydrant c/w Adaptor & Blank Cap

| Model | PH2T |
|-----------------------------|---|
| Inlet | 100 mm Flanged to EN 1092-2 Table 9 |
| Outlet | 2 x 65 mm Male V Blank Cap & Chain |
| Working Pressure | 16 bar |
| Test Pressure | 24 bar |
| Overall Flowrate | 2000 L / min @ 1.7 bar |
| Body Material | Cast Iron** / Ductile Iron to BS 2789 |
| Outlet Material | Copper Alloy to BS 1400 |
| Paint Finishing* | RAL 3000 Flame Red Epoxy Polyester Powder Coating |
| Manufactured & Certified to | JKR 20200-0042-99 |

*Yellow finishing available upon request

**Factory tested



2 Way Fire Hydrant c/w Landing Valve

| Model | PH2Q |
|-----------------------------|---|
| Inlet | 100 mm Flanged to EN 1092-2 Table 9 |
| Outlet | 2 x 65 mm Landing Valve With Female Inst. to BS 336 |
| Working Pressure | 16 bar |
| Test Pressure | 24 bar |
| Overall Flowrate | 2000 L / min @ 1.7 bar |
| Body Material | Cast Iron** / Ductile Iron to BS 2789 |
| Outlet Material | Copper Alloy to BS 1400 |
| Paint Finishing* | RAL 3000 Flame Red Epoxy Polyester Powder Coating |
| Manufactured & Certified to | JKR 20200-0042-99 |

*Yellow finishing available upon request

**Factory tested



2 Way Fire Hydrant c/w Pressure Regulating Valve

| Model | PH2R |
|-----------------------------|---|
| Inlet | 100 mm Flanged to EN 1092-2 Table 9 |
| Outlet | 2 x 65 mm Pressure Regulating Valve With Female Inst. to BS 336 |
| Working Pressure | 20 bar |
| Test Pressure | 30 bar |
| Overall Flowrate | 2000 L / min @ 1.7 bar |
| Body Material | Cast Iron** / Ductile Iron to BS 2789 |
| Outlet Material | Copper Alloy to BS 1400 |
| Paint Finishing* | RAL 3000 Flame Red Epoxy Polyester Powder Coating |
| Manufactured & Certified to | JKR 20200-0042-99 |

*Yellow finishing available upon request

**Factory tested

Top Techno Fire & Safety Co. LLC

